

TECHNICAL DATASHEET

TUBELED 600MM 9W G13 SINGLE T8

03-07-2020



NO IMAGE
AVAILABLE

VO/TUBELED/10W/G13/6500K/600MM/SINGLE/T8 LED TUBE

NOTES

General Informations

Stock Code	1600320
HSC/GTIP Code	8543.70.90.00.19
EAN-13 (Inbox Barcode)	16970233832499
ITF-14 (Outbox Barcode)	6970233832492
Introduction	single-ended LED tubes,another ended with non-bridged &Non Rotatable

Lighting Characteristics

Luminous Flux	775 lumen
Time for 60% of Lumen	<0.6 seconds
Light Beam Angle	320°
Flicker	No
LED Type	SMD

Electrical Characteristics

Current Type	AC
Operation Voltage	100-260 Volt
Operation Frequency	50/60 Hertz
Electrical Current	0,08 Amper
Power	9 Watt
Power Factor	>0.6
Luminous Efficiency	78 lumen/Watt
Energy Savings	0,85
Dimmable	No
Electrical Protection Class	Class II

Mechanical Parameters

Bulb Body Shape	T8
IP Protection Class	IP20
Switch On/Off Cycle	30000
Lifetime	25000 hours
Body Material	Glass Powder
Body Colour	White
Diffuser Material	Glass with powder
Product Height	602 millimeter
Product Width	Ø28 millimeter
Ambient Temperature (Ta)	-20°C<Ta<40°C

Electrical Component Specifications

Component Fitting Type	External Driver
Driver Properties	IC
Driver Input Voltage	100-260 Volt
Driver Input Current	0,08 Amper

Logistic Informations

Inbox Length	29 millimeter
Inbox Width	29 millimeter
Inbox Height	609 millimeter
Outbox Length	650 millimeter
Outbox Width	185 millimeter
Outbox Height	160 millimeter
Outbox Volume	0,01924 m ³
Outbox Quantity	30 pieces
Unit Net Weight	0,095 kilogram
Outbox Net Weight	2,85 kilogram
Outbox Gross Weight	3,47 kilogram

IMPORTANT NOTES: VITO reserves the right to change/remove models or specifications partially/completely without any notice. Information, models and photographs of the products in this technical datasheet can not be used, reproduced or republished without permission. However, some parts can be quoted by giving reference and/or chapter number belonging to technical datasheet. Most of the items in the datasheet have been designed by our company within indicated technical specifications inside. Our company is not responsible for errors caused by wrong installation and operating against rules according to qualifications specified in the product details. Photographs printed in this datasheet may not reflect the actual color of the product depending on printing conditions. In the same context, typographical errors may possibly be found in the texts.