



KMA-36-12-V, s vypínačom  
Obj. kód 30310037

## KMA-V

ochrana proti  
skratu, preťaženiu,  
pracovná teplota:  
-20°C až +45°C

100-240 V

50/60 Hz

IP 20



obj. kód	typ	W	U výstup	I	rozmer (mm)
30310037	KMA-36-12-V	36	12 V	3 A	95x46x32



KMA-24-12, obj. kód 30310024  
KMA-24-24, obj. kód 30320024



KMA-36-12, obj. kód 30310036  
KMA-36-24, obj. kód 30320036



KMA-60-12, obj. kód 30310060  
KMA-60-24, obj. kód 30320060

## KMA

ochrana proti  
skratu, preťaženiu,  
pracovná teplota:  
-20°C až +45°C

100-240 V

50/60 Hz

IP 20



obj. kód	typ	W	U výstup	I	rozmer (mm)
30310024	KMA-24-12	24	12 V	2 A	83x43x30
30310036	KMA-36-12	36	12 V	3 A	95x46x32
30310060	KMA-60-12	60	12 V	5 A	122x60x39
30320024	KMA-24-24	24	24 V	1 A	83x43x30
30320036	KMA-36-24	36	24 V	1,5 A	95x46x32
30320060	KMA-60-24	60	24 V	2,5 A	122x60x39