



Napájacie zdroje LED



KMT-15-12, obj. kód 30410015



KMT-25-12, obj. kód 30410025
KMT-25-24, obj. kód 30420025



KMT-40-12, obj. kód 30410040
KMT-40-24, obj. kód 30420040



KMT-60-12, obj. kód 30410060
KMT-60-24, obj. kód 30420060



KMT-80-12, obj. kód 30410080
KMT-80-24, obj. kód 30420080



KMT-100-12, obj. kód 30410100
KMT-100-24, obj. kód 30420100



KMT-120-12, obj. kód 30410120
KMT-120-24, obj. kód 30420120



KMT-150-12, obj. kód 30410150
KMT-150-24, obj. kód 30420150



KMT-200-12, obj. kód 30410200
KMT-200-24, obj. kód 30420200



KMT-240-12, obj. kód 30410240
KMT-240-24, obj. kód 30420240



KMT-360-12, obj. kód 30410360
KMT-360-24, obj. kód 30420360

KMT

ochrana proti skratu,
pracovná teplota:
-20°C
až +45°C

50/60 Hz

IP 20



obj. kód	typ	W	U	V	I	rozmer (mm)	obj. kód	typ	W	U	V	I	rozmer (mm)
30410015	KMT-15-12	15	170-240V	12	1,25 A	76x40x20	30420025	KMT-25-24	25	100-240V	24	1,05A	85x56x38
30410025	KMT-25-12	25	170-240V	12	2,1 A	85x56x38	30420040	KMT-40-24	40	100-240V	24	1,65A	127x43x35
30410040	KMT-40-12	40	170-240V	12	3,3 A	127x43x35	30420060	KMT-60-24	60	100-240V	24	2,5A	160x40x33
30410060	KMT-60-12	60	170-240V	12	5 A	160x40x33	30420080	KMT-80-24	80	100-240V	24	3,13A	160x40x33
30410080	KMT-80-12	80	170-240V	12	6,67 A	160x40x33	30420100	KMT-100-24	100	100-240V	24	4,17A	200x60x38
30410100	KMT-100-12	100	170-240V	12	8,3 A	200x60x38	30420120	KMT-120-24	120	100-240V	24	5A	200x60x38
30410120	KMT-120-12	120	170-240V	12	10 A	200x60x38	30420150	KMT-150-24	150	100-240V	24	6,25A	200x60x38
30410150	KMT-150-12	150	170-240V	12	12,5 A	200x60x38	30420200	KMT-200-24	200	100-240V	24	8,35A	225x70x40
30410200	KMT-200-12	200	170-240V	12	16,7 A	225x70x40	30420240	KMT-240-24	240	100-240V	24	10A	225x70x40
30410240	KMT-240-12	240	170-240V	12	20 A	225x70x40	30420360	KMT-360-24	360	100-240V	24	15A	225x70x40
30410360	KMT-360-12	360	170-240V	12	30 A	225x70x40							