

Napájacie zdroje LED



KML-12-12, obj. kód 32210012



KML-24-12, obj. kód 32210024
KML-24-24, obj. kód 32220024



KML-36-12, obj. kód 32210036
KML-36-24, obj. kód 32220036



KML-60-12, obj. kód 32210060
KML-60-24, obj. kód 32220060



KML-80-12, obj. kód 32210080
KML-80-24, obj. kód 32220080



KML-100-12, obj. kód 32210100
KML-100-24, obj. kód 32220100

KML

ochrana proti
skratu, preťaženiu,
prepätiu,
pracovná teplota:
-20°C až +45°C

110-240 V

50/60 Hz

IP 20



obj. kód	typ	W	V	I	rozmer (mm)
32210012	KML-12-12	12	12	1 A	89 x 39 x 23
32210024	KML-24-12	24	12	2 A	115 x 44 x 28
32210036	KML-36-12	36	12	3 A	139 x 44 x 28
32210060	KML-60-12	60	12	5 A	166 x 44 x 28
32210080	KML-80-12	80	12	6,67 A	166 x 44 x 28
32210100	KML-100-12	100	12	8,34 A	166 x 46 x 30

obj. kód	typ	W	V	I	rozmer (mm)
32220024	KML-24-24	24	24	1 A	115 x 44 x 28
32220036	KML-36-24	36	24	1,5 A	139 x 44 x 28
32220060	KML-60-24	60	24	2,5 A	166 x 44 x 28
32220080	KML-80-24	80	24	3,33A	166 x 44 x 28
32220100	KML-100-24	100	24	4,17 A	166 x 46 x 30



KMM-12-12, obj. kód 30510012



KMM-40-12, obj. kód 30510040



KMM

ochrana proti
skratu, preťaženiu,
prepätiu,
tepelná ochrana
pracovná teplota:
-20°C až +40°C

220-240 V

50/60 Hz

IP 20



obj. kód	typ	W	V	I	rozmer (mm)
30510012	KMM-12-12	12	12	1 A	90x40x24
30510040	KMM-40-12	40	12	3,3 A	160x58x20